

Specialised Engineering Services

As part of JBK Group, AusLift can design, certify, manufacture & test specialised engineering solutions to meet your unique needs.

For the past 25 years we have been engineering specialised lifting solutions including;

- 25 tonne overhead crane installations for the mining industry
- Various Underground roof mount monorail systems
- 250 tonne x 26m modular spreader beam
- Various specialised lifting & spreader beam

Contact AusLift for all your lifting solutions.



Phone: (02) 4271 6424 | **Fax:** (02) 4272 6424

Address: 6 Investigator Dr. Unanderra NSW 2526

Postal: PO Box 1184 Unanderra 2526 | **Email:** info@jbkgroup.com.au

www.jbkgroup.com.au



Part of the
JBK Engineering
GROUP

www.jbkgroup.com.au

Standard Lifting Beam

Standard Range or purpose designed lifting beams to suit your requirements.

- Capacity range 2 tonne to 300 tonne
- Fully compliant to AS 4991
- Rugged construction
- 3 point lifting for single or double leg lifts
- A range of surface finishes available
- Supplied with proof load test certification

Stock Code	WLL (Tonnes)	L (mm)	D (mm)
LFT-015-2000	1.5	2000	19
LFT-015-3000	1.5	3000	19
LFT-015-4000	1.5	4000	19
LFT-035-2000	3.5	2000	19
LFT-035-3000	3.5	3000	19
LFT-035-4000	3.5	4000	19
LFT-060-2000	6	2000	22
LFT-060-3000	6	3000	22
LFT-060-4000	6	4000	22



Telescoping Spreader Beam

Standard Range or purpose designed spreader beams to suit your requirements.

- Capacity range 2 tonne to 300 tonne
- Fully compliant to AS 4991
- Rugged construction
- 3 point lifting for single or double leg lifts
- A range of surface finishes available
- Supplied with proof load test certification
- Ease of use

Stock Code	WLL (Tonnes)	L (mm)	D (mm)	R (mm)
TEL-020-3600	2	2400-3600	16	100
TEL-050-2000	5	1200-2000	25	100
TEL-050-3000	5	1800-3000	25	100
TEL-050-5000	5	3000-5000	25	100
TEL-050-7000	5	4000-7000	25	100
TEL-080-4200	8	2400-4200	25	100
TEL-100-3200	10	2000-3200	32	100
TEL-120-4000	12	2400-4000	32	100
TEL-150-5000	15	3000-5000	42	100
TEL-200-3600	20	2000-3600	42	100



Spreader Beams

Standard Range or purpose designed spreader beams to suit your requirements.

- Capacity range 2 tonne to 300 tonne
- Fully compliant to AS 4991
- Rugged construction
- Lifting option for single or double leg lifts
- A range of surface finishes available
- Supplied with proof load test certification

Stock Code	WLL (Tonnes)	L (mm)	D (mm)
SPR-030-3000	3	3000	16
SPR-030-4500	3	4500	16
SPR-030-6000	3	6000	16
SPR-030-9000	3	9000	16
SPR-050-3000	5	3000	25
SPR-050-4500	5	4500	25
SPR-050-6000	5	6000	25
SPR-050-9000	5	9000	25
SPR-080-3000	8	3000	25
SPR-080-6000	8	6000	25
SPR-100-3000	10	3000	32
SPR-100-6000	10	6000	32



Combination Beam

Standard Range or purpose designed spreader beams to suit your requirements.

- Capacity range??? tonne
- Fully compliant to AS 4991
- Rugged construction
- 3 point lifting for single or double leg lifts
- A range of surface finishes available
- Supplied with proof load test certification
- Ease of use

Stock Code	Max. WLL (Spreader)	Max. WLL (Spreader)	L (mm)	D (mm)	R (mm)
COM-086-3600	8.6	1.6	2100-3600	25	100
COM-100-3600	10	1.5	2100-3600	32	100
COM-100-5000	10	1.6	3000-5000	32	100
COM-150-4000	15	3.6	2600-4000	42	100
COM-150-6000	15	2.1	4000-6000	42	100
COM-200-6000	20	3.2	4000-6000	42	100

